



## ***BP-P260/BP-P340 Desktop Label Printer***

---

- Thermal transfer and direct thermal 4 inch wide label printer
- Suitable for product labeling, packaging and information tags
- Large 300M ribbon capacity 5" internal label roll
- High speed performance and customize options available
- 32bit CPU, USB 2.0 Port Standard
- Available in 200 dpi 300 dpi versions

# BP-P260 / BP-P340

Desktop Label Printer

	BP-P260	BP-P340
<b>Resolution</b>	203 dpi (8 dot/mm)	300 dpi (12 dot/mm)
<b>Print Method</b>	Thermal Transfer / Direct Thermal	
<b>CPU</b>	32 Bit	
<b>Memory</b>	4 MB Flash (2MB for user storage), 8 MB SDRAM	
<b>Print Speed</b>	6 IPS (150 mm/s)	4 IPS (100 mm/s)
<b>Print Length</b>	Min 4 mm (0.16")	Min 4 mm (0.")
	Max 1727 mm (68")	Max 762mm (30")
<b>Print Width</b>	108 mm (4.25")	105.7 mm (4.16")
<b>Sensor Type</b>	Adjustable reflective; Fixed transmissive, center aligned	
<b>Sensor Detection</b>	Type : Label gap and black mark sensing	
	Detection : Label length auto sensing and / or program command setting	
<b>Media</b>	Label Roll OD: Max. 127 mm (5")	
	Core Diameter : 1", 1.5", 3"	
	Width : 25.4 mm (1") ~ 118 mm (4.64")	
	Thickness : 0.06 mm ~ 0.25 mm (0.003 ~ 0.01)	
<b>Ribbon</b>	Length : 300 M (981 ft)	
	Max. Ribbon roll OD : 68 mm (2.67")	
	Ribbon width : 30 mm ~ 110 mm (1.18"~4.33")	
	Core Inner Diameter : 25.4 mm (1")	
	Types: Wax, wax/resin, resin	
<b>Printer Language</b>	EZPL (Firmware downloadable)	
<b>Software</b>	DLL & Driver : Microsoft Windows 2000, XP and Vista	
<b>Resident Fonts</b>	11 resident alphanumeric fonts (included OCR A & B), those are expandable 8 times horizontally and vertically. All bit mapped fonts in 8 orientations. Scalable Font (Code Page 850 & 852) in 4 orientations	
<b>Download Fonts</b>	Windows bit mapped in 8 orientations. True type font (Ver. 2.XX) and Asian fonts in 4 orientations	
<b>Image Handling</b>	BMP, PCX, Support ICO, WMF, JPG, EMF file through software	
<b>Barcodes</b>	Code 39, Code 93, Code 128, (Subset A,B,C), UCC/EAN-128 K-Mart, UCC/EAN-128, UPC A/E (add on 2 & 5), I 2 of 5, I 2 of 5 with Shipping Bearer Bars, EAN 8/13 (add on 2 & 5), Codabar, Post NET, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Post Code, RPS 128, PDF 417, Datamatrix code & QR code	
<b>Interfaces</b>	Serial port : RS-232 (Baud rate : 4800 ~ 115200, Xon / Xoff, DSR / DTR)	
	USB port: V2.0	
	Parallel port : Bi-direction	
<b>Control Panel</b>	Three mono-color status: Power on, Ribbon out, Meida out	
	Control keys: FEED, PAUSE and CANCEL	
<b>Power</b>	Auto Switching 100/240 VAC, 50/60 Hz	
<b>Enviornment</b>	Operation : 41°F to 104°F (5°C to 40°C)	
	Storage : -4°F to 122°F (-20°C to 50°C)	
<b>Humidity</b>	Operation : 30-85%, non-condensing,	
	Storage : 10-90%, non-condensing	
<b>Cert. Approval</b>	CE, FCC Class A, CCC, CB, cUL	
<b>Printer Dimension</b>	Length : 285 mm (11.2") / Height : 171 mm (6.8")	
	Width : 226 mm (8.9") / Weight : 3 Kg	
<b>Options</b>	Rotary Cutter	
	label Dispenser	
	External label roll holder for 250mm OD label rolls	
	External label rewinder	
	802.11 b/g wireless print server (Default off; disables USB when in use. Must remove PS2 port and Ethernet card to install)	

ATIDB052(E)\_1210